

Function					API Definition							
Cluster	Operation	Variant	AFD structure	Meaning	Method	Path / Endpoint	Function variant (APIVAR code)	Request payload	Request function	Parameters (query)	Response payload (* = payload not required)	Response function
message	new	<default>	messageStructure	Peer to peer mailbox: Direct transmission of an electronic message (peer to peer) without the need for an intermediary service	POST	/messages/new	A0500 - newMessage	messageStructure	newMessage_request		HTTP statusCode	
message	retrieve	<default>	messageStructure	Peer to peer mailbox: Client request to obtain all available messages.	GET	/messages/retrieve	A0502 - retrieveMessage			message-subject, message-context, message-function (all are optional)	[messageStructure]	retrieveMessage_response
message	retrieve	list	messageStructure	Peer to peer mailbox: Client request to obtain a list of available messages. Only the commonFunctional and commonTechnical of the messages will be returned.	GET	/messages/list	A0504 - retrieveMessageList			message-subject, message-context, message-function (all are optional)	[messageStructure]	retrieveMessageList_response
session	initiate	<default>	claimStructure	Request for a url to initiate a browser session with prefilled data.	POST	/claims/initiate-session	A0550 - initiateSession	claimStructure	initiateSession_request		URL	
session	initiate	<default>	loanStructure	Request for a url to initiate a browser session with prefilled data.	POST	/loans/initiate-session	A0550 - initiateSession	loanStructure	initiateSession_request		URL	
session	initiate	<default>	partyStructure	Request for a url to initiate a browser session with prefilled data.	POST	/parties/initiate-session	A0550 - initiateSession	partyStructure	initiateSession_request		URL	
session	initiate	<default>	pensionStructure	Request for a url to initiate a browser session with prefilled data.	POST	/pensions/initiate-session	A0550 - initiateSession	pensionStructure	initiateSession_request		URL	
session	initiate	<default>	policyStructure	Request for a url to initiate a browser session with prefilled data.	POST	/policies/initiate-session	A0550 - initiateSession	policyStructure	initiateSession_request		URL	